


INGROUND55 (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	4W	
Luminaire	Up to 450lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	350mA	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Stainless Steel - 30	

DESCRIPTION

Construction

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.

Electrical & Optics

- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 3/16" thermal-shock resistant tempered glass.
- To be operated only with constant current 350mA Class 2 remote drivers (order separately).

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP68 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- 1000Kg static load capacity per EN60598.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Supplied with recessed installation box made of engineering plastic.
- Other recessed installation boxes made of engineering plastic or of AISI 316L stainless steel available.
- Supplied with power cord. 22AWG conductors.

IP68 40"











VERSIONS (Click on below link to configure your product)





trim flush with ground trim above the ground

Size: Size: Ø 2" 5/32 Ø 2" 17/32 3" 15/16 3" 3/4 4" 11/32

OPTICS







See accessories in the next page



THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099227X**Code Ref. **07293**



TECHNICAL INFORMATION

Weight 0.18 lb

STAINLESS STEEL AISI 316L INSTALLATION BOX.

Arcluce Code **1099225X** Code Ref. **07295**



TECHNICAL INFORMATION

Weight 1.32 lb

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099226X** Code Ref. **07299**



TECHNICAL INFORMATION

Weight 0.13 lb