


## PIXOL150 (Model)



#### **TECHNICAL INFORMATION**

Listings

Installation

Wall mounted.

rawlplugs.

(accessory).

locations (cULus mark).

Rated IP66 per EN60598.

>60000 hours at L80.

Watt	31W
Luminaire	Up to 3400lm
сст	3000K – 4000K
CRI	>80
Wiring	120-277V 60Hz 0-10V
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	White - 11 / Grey - 16 / Aluminium - 21

UL certified to U.S. and Canadian standards, suitable for wet

Luminaire rated for -25°C minimum ambient temperature.

 High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life</li>

Die-cast aluminium base (EN 47100) for anchoring with

Universal plate for mounting on standard junction boxes

Spacer for side-entry of conduits (accessory).

#### DESCRIPTION


#### Construction

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

#### **Electrical & Optics**

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 3/16" thermal-shock resistant tempered glass.
- Driver protected against voltage surges up to 5kV.

#### VERSIONS (Click on below link to configure your product)



Size:	
5" 29/32	
5" 29/32	
3" 15/16	

<u>twoway</u>
Size:
5" 29/32
5" 29/32

3" 15/16

#### OPTICS

oneway



# IP66

IES Files 🕁



<u></u> ⇒)	
(	$\exists$

(UL)
CERTIFIED



#### PLATE FOR PIXOL INSTALLATION

Arcluce Code 1099622X Code Ref.

#### **TECHNICAL INFORMATION**

Weight 1.1 lb

#### BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - WHITE

Arcluce Code **1099626X-11** Code Ref.

#### **TECHNICAL INFORMATION**

Color	White - 11
Weight	1.76 lb

### BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - GREY, SIMILAR TO (RAL 7024) Arcluce Code 1099626X-16

Arcluce Code **109962** Code Ref.

#### **TECHNICAL INFORMATION**

Color	Grey - 16
Weight	1.76 lb

#### BASE PLATE FOR WALL/CEILING APPLICATION FOR SIDE ENTRY OF POWER CABLE - ALUMINIUM (RAL 9005)

Arcluce Code Code Ref.	1099626X-21		
	TECHNICAL INFO	ORMATION	
	Color	Aluminium - 21	

Weight 1	1.76 lb