

# CONO (Model)



## TECHNICAL INFORMATION

[IES Files](#) 

<b>Watt</b>	35W
<b>Luminaire</b>	Up to 5250lm
<b>CCT</b>	3000K – 4000K - DarkSky approved for CCTs of 3000K or lower
<b>CRI</b>	>80
<b>Wiring</b>	120-277V 60Hz / 0-10V
<b>LED life time</b>	> 60000h - L80 - B20 (Ta 25°C)
<b>Color</b>	Grey - 16 / Aluminium - 21

## DESCRIPTION

### Construction

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### Electrical & Optics

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 3/16" thermal-shock resistant tempered glass.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- DarkSky approved for CCTs of 3000K or lower.
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

### Installation

- Bracket installation (Ø60mm tenon).

IP66

IK08

CERTIFIED

0,07 m<sup>2</sup>

## VERSIONS (Click on below link to configure your product)

[comfort](#)[performance](#)

Size:


Ø 11" 13/16  
13"

Size:

Ø 11" 13/16  
13"



## OPTICS




See accessories in the next page

## PAINTED DIE-CAST ALUMINIUM WALL BRACKET FOR Ø 60 MM ARM.

Arcluce Code **1099086X-16**

Code Ref.



## TECHNICAL INFORMATION


**Color** Grey - 16

**Weight** 1.9 lb

## PAINTED STEEL Ø 60 MM ARM.

Arcluce Code **1099067X-16**

Code Ref.



## TECHNICAL INFORMATION


**Color** Grey - 16

**Weight** 15.65 lb

## POLE ATTACHMENT FOR 1 LIGHT FITTING.

Arcluce Code **1099071X-16**

Code Ref.



## TECHNICAL INFORMATION


**Color** Grey - 16

**Weight** 3.97 lb

## PAINTED DIE-CAST ALUMINIUM DOUBLE POLE ATTACHMENT.

Arcluce Code **1099073X-16**

Code Ref.



## TECHNICAL INFORMATION


**Color** Grey - 16

**Weight** 5.14 lb

## DOUBLE POLE ATTACHMENT WITH CURVED ARMS IN PAINTED STEEL.

Arcluce Code **1099425X-16**

Code Ref.




## TECHNICAL INFORMATION

**Color** Grey - 16**Weight** 12.46 lb

## SINGLE POLE ATTACHMENT WITH CURVED ARM IN PAINTED STEEL.

Arcluce Code **1099424X-16**

Code Ref.




## TECHNICAL INFORMATION

**Color** Grey - 16**Weight** 6.17 lb

## PAINTED DIE-CAST ALUMINIUM WALL BRACKET FOR Ø 60 MM ARM.

Arcluce Code **1099086X-21**

Code Ref.




## TECHNICAL INFORMATION

**Color** Aluminium - 21**Weight** 1.9 lb

## PAINTED STEEL Ø 60 MM ARM.

Arcluce Code **1099067X-21**

Code Ref.




## TECHNICAL INFORMATION

**Color** Aluminium - 21**Weight** 15.65 lb

## PAINTED DIE-CAST ALUMINIUM SINGLE POLE ATTACHMENT.

Arcluce Code **1099071X-21**

Code Ref.




## TECHNICAL INFORMATION

**Color** Aluminium - 21**Weight** 3.97 lb

## PAINTED DIE-CAST ALUMINIUM DOUBLE POLE ATTACHMENT.

Arcluce Code **1099073X-21**

Code Ref.




## TECHNICAL INFORMATION

**Color** Aluminium - 21**Weight** 5.14 lb

## DOUBLE POLE ATTACHMENT WITH CURVED ARMS IN PAINTED STEEL.

Arcluce Code **1099425X-21**

Code Ref.




## TECHNICAL INFORMATION

**Color** Aluminium - 21**Weight** 12.46 lb

## SINGLE POLE ATTACHMENT WITH CURVED ARM IN PAINTED STEEL.

Arcluce Code **1099424X-21**

Code Ref.



## TECHNICAL INFORMATION

**Color** Aluminium - 21**Weight** 6.17 lb