INGROUND110 short (Model)

TECHNICAL INFORMATION

IES Files

Watt	4W
Luminaire	Up to 575lm
CCT	3000K – RGBW
CRI	>80
Wiring	
LED life time	> 60000h - L80 - B20 (Ta 25°C), > h - L - B (Ta 25°C)
Color	Stainless Steel - 30

DESCRIPTION

VERSIONS *(Click on below link to configure your product)*

round trim above the ground
Size:
Ø 4" 11/16
2" 7/8
7" 15/32

squared trim above the ground
Size:
2" 7/8
7" 15/32
4" 23/32

round trim flush with ground
Size:
Ø 4" 11/32
2" 7/8
7" 15/32

OPTICS

IP67
IK09
III
LB 4400

See accessories in the next page

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099217X**
Code Ref.



TECHNICAL INFORMATION

Weight	0.31 lb

IP68 LINEAR JOINT - 2 WAYS - 2 POLES.

Arcluce Code **1099408X**
Code Ref.

TECHNICAL INFORMATION

Weight	0.07 lb

JUNCTION BOX IP68 - 4 WAYS - 2/3 POLES.

Arcluce Code **1099259X**
Code Ref.



TECHNICAL INFORMATION

Weight	0.11 lb

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX WITH AISI 316L STAINLESS STEEL COUNTER-RING.

Arcluce Code **1099218X**
Code Ref.



TECHNICAL INFORMATION

Weight	0.53 lb

JUNCTION BOX IP68 - 4 WAYS - 4/5 POLES.

Arcluce Code **1099407X**
Code Ref.

TECHNICAL INFORMATION

Weight	0.18 lb

Arcluce Code **1098009X**
Code Ref.

TECHNICAL INFORMATION

Weight	1.1 lb

Arcluce Code **1098010X**
Code Ref.

TECHNICAL INFORMATION

Weight	1.1 lb