TECHNICAL INFORMATION



INGROUND260 (Model)



TECHNICAL	<u>IES Files</u> ↓	
Watt	15W	
Luminaire	Up to 1450lm	
ССТ	3000K – 4000K	

Luiiiiiaiie	ορ το 1430iiii	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	120-277V 60Hz / DALI, 120V 60Hz, 120-277V 60Hz / 0-10V	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Stainless Steel - 30	

DESCRIPTION

Construction

- Die-cast aluminium body (EN 47100).
- AISI 316L stainless steel trim.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Reflector made of engineering plastic metalized in high-
- Screen made of 19/32" thermal-shock resistant tempered glass.

Listings

- Intertek certified to U.S. and Canadian standards suitable for wet locations (ETL mark).
- Rated IP67 per EN60598.
- Luminaire rated for -20°C minimum ambient.
- 6000Kg static load capacity per EN60598.
- Can be driven over at maximum speed 20Km/h per EN60598.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Double cable gland PG16 for through wiring.
- Supplied with recessed installation box made of engineering plastic.
- Upon request fixtures can be supplied with anti-slip glass.











VERSIONS (Click on below link to configure your product)



round trim above the ground

Size: Ø 10" 13/16

16" 3/8 16" 3/8



squared trim above the ground

Size:

10" 13/16

OPTICS








GLASS LENS FOR ELLIPTIC BEAM.

Arcluce Code

1099253X

Code Ref.



TECHNICAL INFORMATION


Weight 0.6 lb

PAINTED DIE-CAST ALUMINIUM DIRECTIONAL LOUVRE FOR GLARE CONTROL.

Arcluce Code

1099110X-12

Code Ref.



TECHNICAL INFORMATION


Color	Black - 12
Weight	0.51 lb

PAINTED DIE-CAST ALUMINIUM GLARE-CONTROL LOUVRED.

Arcluce Code

1099108X-12

Code Ref.



TECHNICAL INFORMATION


Color Black - 12
Weight 0.4 lb

ANTI-SLIP OPAL GLASS.

Arcluce Code

1099283X

Code Ref.



TECHNICAL INFORMATION

Weight 3.59 lb



THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code 1099211X Code Ref.



TECHNICAL INFORMATION

Weight 2.2 lb