

KOMPASS Bollard (Model)



TECHNICAL INFORMATION

[IES Files](#)

| | |
|----------------------|--------------------------------|
| Watt | 4W – 30W |
| Luminaire | Up to 425lm |
| CCT | 3000K – 4000K |
| CRI | >80 |
| Wiring | 120-277V 60Hz |
| LED life time | > 60000h - L80 - B20 (Ta 25°C) |
| Color | Aluminium - 21 / Grey - 16 |

DESCRIPTION

Construction

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Screen made of 5/16" thermal-shock resistant tempered glass.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Suitable for mounting within 1.2 m (4 ft) of ground.
- Rated IP66 per EN60598.
- Luminaire rated for -20°C minimum ambient.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Surface installation.
- Die-cast aluminium base (EN 47100) for anchoring with rawlplugs.

IP66




VERSIONS *(Click on below link to configure your product)*



[comfort+](#)

Size:
5" 29/32
4" 1/32
19" 11/32 to 42" 13/32



[comfort](#)

Size:
5" 29/32
4" 1/32
19" 11/32 to 42" 13/32

OPTICS

