

KOMPASS Bollard (Model)



TECHNICAL INFORMATION

[IES Files](#) 

Watt	5W – 30W
Luminaire	Up to 350lm
CCT	3000K – 4000K
CRI	>80
Wiring	
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	Grey - 16 / Aluminium - 21

DESCRIPTION



VERSIONS *(Click on below link to configure your product)*



[comfort](#)



[comfort+](#)

Size:
5" 29/32
4" 1/32
19" 11/32 to 42" 13/32

Size:
5" 29/32
4" 1/32
19" 11/32 to 42" 13/32




OPTICS



See accessories in the next page

ZINC-COATED AND PAINTED STEEL BASE PLATE WITH ZINC-COATED STEEL STUD BOLTS. 350 MM HIGH.


Arcluce Code **1099400X-16**
Code Ref.



TECHNICAL INFORMATION	
Color	Grey - 16
Weight	2.2 lb

HOT-DIPPED ZINC-COATED STEEL BASEMENT FOR GROUND ANCHORING.

Arcluce Code **1099429X**
Code Ref.



TECHNICAL INFORMATION	
Color	Chrome - 31
Weight	2.65 lb

IP68 LINEAR JOINT - 2 WAYS - 3 POLES.


Arcluce Code **1099409X**
Code Ref.



TECHNICAL INFORMATION	
Weight	0.07 lb

ZINC-COATED AND PAINTED STEEL BASE PLATE WITH ZINC-COATED STEEL STUD BOLTS. 350 MM HIGH.

Arcluce Code **1099400X-21**
Code Ref.



TECHNICAL INFORMATION	
Color	Aluminium - 21
Weight	2.2 lb