

# KOMPASS Wall (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	20W – 40W	
Luminaire	Up to 2950lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	120-277V 60Hz 0-10V	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Grey - 16 / Aluminium - 21	

### **DESCRIPTION**

#### Construction

- Extruded aluminium body.
- Die-cast aluminium caps (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### **Electrical & Optics**

- 0-10V dimming available.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 5/16" thermal-shock resistant tempered glass

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -20°C minimum ambient.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

#### Installation

- Wall mounted.
- Die-cast aluminium base (EN 47100) for anchoring with rawlplugs.
- Universal plate for mounting on standard junction boxes.









# VERSIONS (Click on below link to configure your product)



kompass wall

Size: 4" 1/32 5" 29/32

19" 11/32 to 30" 7/8

## **OPTICS**

