

TECHNICAL INFORMATION

Watt	29W – 80W		
Luminaire	Up to 8400lm		
сст	3000K – 4000K - DarkSky approved for CCTs of 3000K or lower		
CRI	>80		
Wiring	120-277V 60Hz / 0-10V		
LED life time	> 60000h - L80 - B20 (Ta 25°C)		
Color	Grey - 16 / Black - 12 / Aluminium - 21 / Dark bronze - 26		

DESCRIPTION

Construction

- Die-cast aluminium body (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Reflector made of anodized aluminium with non-iridescent specular finishing.
- Screen made of 3/16" thermal-shock resistant tempered glass.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.
- DarkSky approved for CCTs of 3000K or lower.

Installation

- Post-top installation (Ø 2" 3/8 tenon).
- Available wired with Zhaga Book 18 or NEMA ANSI C136.41 (5-pin) and waterproof cover. For the Zhaga Book 18 version add at the end of the code the suffix "ZU" for the version with adapter at the top, or "ZD" for the version with adapter at the bottom, or "ZB" for the version with adapter both at the top and at the bottom. For the NEMA ANSI C136.41 version, add the suffix "NU" at the end of the code for the version with adapter at the top.



IP66

IES Files ↓





VERSIONS (Click on below link to configure your product)




<u>clear glass</u>



opal glass

Size: Ø 20" 15/32 14" 27/32 Size: Ø 20" 15/32 14" 27/32

OPTICS



See accessories in the next page



Generated on: 08-27-2025 3:05 pm



PAINTED DIE-CAST ALUMINIUM SINGLE POLE ATTACHMENT.

Arcluce Code 1099097X-16 Code Ref.

	TECHNICAL IN	ORMATION	
	Color	Grey - 16	
	Weight	7.72 lb	

PAINTED DIE-CAST ALUMINIUM DOUBLE POLE ATTACHMENT.

Arcluce Code **1099096X-16** Code Ref.

TECHNICAL IN	FORMATION		
Color	Grey - 16		
Weight	13.23 lb		

STRAIGHT POLE COVER 3' ANTH.

Arcluce Code Code Ref.	X-CO03SCUS-16 1099385X-16US			
	TECHNICAL IN	FORMATION		
	Color	Grey - 16		

TAPERED POLE COVER 3' ANTH.

Arcluce Code Code Ref.	X-CO03TCUS-16 1099386X-16US			
	TECHNICAL INFO	RMATION		
	Color	Grey - 16		



PAINTED DIE-CAST ALUMINIUM WALL BRACKET FOR Ø 60 MM ARM.

Arcluce Code 1099098X-12 Code Ref.

	TECHNICAL INI	FORMATION
	Color	Black - 12
	Weight	5.51 lb

PAINTED DIE-CAST ALUMINIUM SINGLE POLE ATTACHMENT.

Arcluce Code 1099097X-12 Code Ref.

		TECHNICAL IN	FORMATION		
	Color	Black - 12			
	Weight	7.72 lb			
A	<u>с</u>				

PAINTED DIE-CAST ALUMINIUM DOUBLE POLE ATTACHMENT.

Arcluce Code Code Ref. 1099096X-12

Color	Black - 12	
Weight	13.23 lb	

PAINTED DIE-CAST ALUMINIUM SINGLE POLE ATTACHMENT.

Arcluce Code Code Ref.	1099097X-21		
	TECHNICAL INI	RMATION	
	Color	Aluminium - 21	
	Weight	7.72 lb	



PAINTED DIE-CAST ALUMINIUM DOUBLE POLE ATTACHMENT.

Arcluce Code **1099096X-21** Code Ref.

	TECHNICAL IN	FORMATION
	Color	Aluminium - 21
	Weight	13.23 lb
<u>⊢A</u> <u>−</u> <u>−</u> <u>−</u> <u>−</u> − <u>−</u> <u>−</u>		

STRAIGHT POLE COVER 3' ALUM.

Arcluce Code Code Ref.	X-CO03SCUS-21 1099385X-21US TECHNICAL INF	ORMATION	
	Color	Aluminium - 21	

TAPERED POLE COVER 3' ALUM.

Arcluce Code Code Ref.	X-CO03TCUS-21 1099386X-21US	
	TECHNICAL IN	ORMATION
	Color	Aluminium - 21

PAINTED DIE-CAST ALUMINIUM SINGLE POLE ATTACHMENT.

Arcluce Code Code Ref.	1099097X-26			
	TECHNICAL INF	TECHNICAL INFORMATION		
		Dark bronze - 26		
	Weight	7.72 lb		



PAINTED DIE-CAST ALUMINIUM DOUBLE POLE ATTACHMENT.

Arcluce Code **1099096X-26** Code Ref.

	TECHNICAL IN	TECHNICAL INFORMATION	
	Color	Dark bronze - 26	
	Weight	13.23 lb	
⊢ <mark>A</mark> ⊢ C – – – – – – – – – – – – – – – – – –			

STRAIGHT POLE COVER 3' D.BRONZE

X-CO03SCUS-26 1099385X-26US					
TECHNICAL IN	TECHNICAL INFORMATION				
Color	Dark bronze - 26				
	TECHNICAL IN				

TAPERED POLE COVER 3' D.BRONZE

Arcluce Code	X-CO03TCUS-26
Code Ref.	1099386X-26US



TECHNICAL INFORMATION

Color Dark bronze - 26