

MOTO3 (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	38W	
Luminaire	Up to 4050lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	120-277V 60Hz DALI, 120-277V 60Hz / 0-10V	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Black - 12 / Grey - 16 / Aluminium - 21	

DESCRIPTION

Construction

- Die-cast aluminium body (EN 47100).
- Die-cast aluminium control gear box (EN 47100).
- Cover made of powder coated sheet steel.
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- 0-10V dimming available.
- Driver protected against voltage surges up to 6kV.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Reflector made of engineering plastic metalized in highvacuum.
- PMMA lenses for LEDs.
- Screen made of 5/16" thermal-shock resistant tempered glass.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.



IK10

IP66

Installation

Ceiling installation.

VERSIONS (Click on below link to configure your product)



1 module

Size:

7" 25/32

9" 1/16

7" 25/32

OPTICS









