

NAPO (Model)



TECHNICAL INFORMATION

[IES Files](#) 

Watt	0.4W – 4W
Luminaire	Up to 225lm
CCT	3000K – 4000K
CRI	>80
Wiring	24V
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	White - 11 / Aluminium - 21

DESCRIPTION

Construction

- Turned aluminium body.
- Polyester powder paint resistant to UV rays.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- To be operated only with constant voltage 24Vdc Class 2 remote drivers (order separately).
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Opal PMMA screen.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP66 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Steel spring clips.
- Supplied with recessed installation box made of engineering plastic.
- Supplied with power cord. 22AWG conductors.


IP66



VERSIONS *(Click on below link to configure your product)*


[trimless](#)

Size:
 Ø 1" 31/32
 3" 15/16
 0" 5/8


[with trim](#)

Size:
 Ø 2" 3/4
 3" 15/16
 0" 25/32


OPTICS



See accessories in the next page

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code **1099226X**
Code Ref.



TECHNICAL INFORMATION

Weight 0.13 lb
