
PIXOL200 (Model)



TECHNICAL INFORMATION

Listings

Installation

locations (cULus mark).

Rated IP66 per EN60598.

>60000 hours at L80.

Galvanized and painted steel bracket.

Supplied with power cord (18AWG conductors).

Surface installation.

Watt	25W – 42W	
Luminaire	Up to 5100lm	
сст	3000K – RGBW	
CRI	>80	
Wiring	120-277V 60Hz 0-10V,	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Grey - 16 / Aluminium - 21	

UL certified to U.S. and Canadian standards, suitable for wet

Luminaire rated for -25°C minimum ambient temperature.

High quality LED sources characterized according to IES

Possibility for double cable gland M20 for through wiring.

TM-30, with high color consistency <3SDCM and long useful life

DESCRIPTION

Construction

- Die-cast aluminium body and trim (EN 47100).
- Double layer polyester powder paint resistant to corrosion and salt spray fog.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- Universal input voltage: 120-277V 50/60Hz.
- 0-10V dimming available.
- Wiring on removable galvanized steel tray.
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- Reflector made of engineering plastic metalized in highvacuum.
- Screen made of 3/16" thermal-shock resistant tempered glass.
- Driver protected against voltage surges up to 5kV.
- PMMA lenses for LEDs for RGBW versions.

VERSIONS (Click on below link to configure your product)



performance

Size:

9" 27/32 6" 5/16 7" 7/8

OPTICS





IP66

	9
CER	TIFIED
	-

Γ	
	\neg
	0.32ft ²

See accessories in the next page



IES Files 🕁



PAINTED DIE-CAST ALUMINIUM AND STEEL SINGLE POLE ATTACHMENT (Ø 102 MM).

Arcluce Code **1099472X-16** Code Ref.

C	\bigcirc	TECHNICAL INFORMATION		
		Color	Grey - 16	
	(Weight	3.75 lb	

PAINTED DIE-CAST ALUMINIUM AND STEEL DOUBLE POLE ATTACHMENT (Ø 102 MM) .

Arcluce Code **1099473X-16** Code Ref.

	\bigcirc	TECHNICAL IN	TECHNICAL INFORMATION		
	A	Color	Grey - 16		
		Weight	4.63 lb		
	C m				

PAINTED STEEL SUPPORT BRACKET FORROOF EAVES.

Arcluce Code Code Ref. 1099154X-16



TECHNICAL INFORMATION		
Color	Grey - 16	
Weight	1.76 lb	

PAINTED DIE-CAST ALUMINIUM AND STEEL SINGLE POLE ATTACHMENT (Ø 102 MM).

Arcluce Code **1099472X-21** Code Ref.



TECHNICAL INFORMATION		
Color	Aluminium - 21	

Weight 3.75 lb



PAINTED DIE-CAST ALUMINIUM AND STEEL DOUBLE POLE ATTACHMENT (Ø 102 MM) .

Arcluce Code **1099473X-21** Code Ref.

() ()	\bigcirc	TECHNICAL IN	FORMATION
	A	Color	Aluminium - 21
	(Weight	4.63 lb

PAINTED STEEL SUPPORT BRACKET FORROOF EAVES.

Arcluce Code **1099154X-21** Code Ref.



TECHNICAL INFORMATION

Color	Aluminium - 21
Weight	1.76 lb