

RAY180 short (Model)



TECHNICAL INFORMATION

[IES Files](#) 

Watt	12W – 20W
Luminaire	Up to 2250lm
CCT	3000K – RGBW
CRI	>80
Wiring	
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	Grey - 16 / Stainless Steel - 30 / Aluminium - 21 / White - 11

DESCRIPTION



VERSIONS *(Click on below link to configure your product)*



[stainless steel trim](#)



[die-cast aluminium trim](#)

Size:
Ø 7" 15/32
3" 31/32

Size:
Ø 7" 15/32
3" 31/32




OPTICS



See accessories in the next page

JUNCTION BOX IP68 - 4 WAYS - 2/3 POLES.

Arcluce Code **1099259X**
Code Ref.



TECHNICAL INFORMATION

Weight 0.11 lb

IP68 LINEAR JOINT - 2 WAYS - 3 POLES.

Arcluce Code **1099409X**
Code Ref.




TECHNICAL INFORMATION

Weight 0.07 lb

PAINTED STEEL GLARE-CONTROL LOUVRED.

Arcluce Code **1099324X**
Code Ref.



TECHNICAL INFORMATION

Weight 1.32 lb

Arcluce Code **1098009X**
Code Ref.



TECHNICAL INFORMATION

Weight 1.1 lb

Arcluce Code **1098010X**
Code Ref.



TECHNICAL INFORMATION

Weight 1.1 lb

JUNCTION BOX IP68 - 4 WAYS - 4/5 POLES.

Arcluce Code **1099407X**
Code Ref.



TECHNICAL INFORMATION

Weight 0.18 lb
