

STONE25 (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	2W	
Luminaire	Up to 20lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	700mA	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Stainless Steel - 30	

DESCRIPTION

Construction

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.

Electrical & Optics

- To be operated only with constant current 700mA Class 2 remote drivers (order separately).
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Clear PMMA screen.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP68 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- 1000Kg static load capacity per EN60598.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Supplied with recessed installation box made of engineering plastic.
- Other recessed installation boxes made of engineering plastic or of AISI 316L stainless steel available.
- Supplied with power cord. 22AWG conductors.











VERSIONS (Click on below link to configure your product)







radial

Size: Ø 1" 11/32 3" 3/4 4" 11/32



OPTICS

Ø 1" 11/32

3" 3/4

4" 11/32







Ø 1" 11/32

3" 3/4

4" 11/32

See accessories in the next page



THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code

1099223X

Code Ref.



TECHNICAL INFORMATION


0.13 lb Weight

STAINLESS STEEL AISI 316L INSTALLATION BOX.

Arcluce Code

1099221X

Code Ref.



TECHNICAL INFORMATION

0.46 lb Weight

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code

1099222X

Code Ref.



TECHNICAL INFORMATION

Weight

0.04 lb