

STONE55 (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	2W	
Luminaire	Up to 100lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	700mA	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Stainless Steel - 30	

DESCRIPTION

Construction

- construction die-cast aluminium body and trim (en 47100).
- construction polyester powder paint resistant to uv rays.

Electrical & Optics

- electrical & optics recessed installation in a special outer casing (included in the package) in glass-fibre reinforced plastic material or in aisi 316l stainless steel. it is possible to pre-order the outer boxes to prepare the system.
- electrical & optics double cable gland pg16 for through wiring.
- electrical & optics supplied with power cable (0.7m).

Listings

- listings this is a listing in english
- listings this is another listing in english

Installation

- installation this is an installation in english
- installation this is another installation in english















VERSIONS (Click on below link to configure your product)



grazing - oneway

Size: Ø 2" 17/32 3" 3/4 4" 11/32



grazing - twoway

Size: Ø 2" 17/32 3" 3/4 4" 11/32



grazing - radial

Size: Ø 2" 17/32 3" 3/4 4" 11/32

OPTICS









THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code

1099227X

Code Ref.



TECHNICAL INFORMATION

0.18 lb Weight

STAINLESS STEEL AISI 316L INSTALLATION BOX.

Arcluce Code

1099225X

Code Ref.



TECHNICAL INFORMATION


Weight 1.32 lb

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code

1099226X

Code Ref.



TECHNICAL INFORMATION

Weight

0.13 lb