


THUNDER55 (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	2W – 4W	
Luminaire	Up to 450lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	ICC 350mA, ICC 700mA	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Stainless Steel - 30	

DESCRIPTION

Construction

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.

Electrical & Optics

- To be operated only with constant current 350mA Class 2 remote drivers (order separately).
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 3/16" thermal-shock resistant tempered glass or opal PMMA screen.

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP68 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Recessed installation.
- Supplied with recessed installation box made of engineering
- Other recessed installation boxes made of engineering plastic or of AISI 316L stainless steel available.
- Supplied with power cord. 22AWG conductors.





IP68 40"




VERSIONS (Click on below link to configure your product)



grazing - oneway

Size: Ø 2" 17/32 3" 3/4 4" 11/32



grazing - twoway

Size: Ø 2" 17/32 3" 3/4 4" 11/32



grazing - radial

Size: Ø 2" 17/32 3" 3/4 4" 11/32



flush trim

Size: Ø 2" 5/32 3" 15/16



relief trim

Size: Ø 2" 17/32 3" 3/4 4" 11/32

OPTICS









See accessories in the next page



THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code

1099227X

Code Ref.



TECHNICAL INFORMATION

0.18 lb Weight

STAINLESS STEEL AISI 316L INSTALLATION BOX.

Arcluce Code

1099225X

Code Ref.



TECHNICAL INFORMATION

Weight 1.32 lb

THERMOPLASTIC MATERIAL RECESSED INSTALLATION BOX.

Arcluce Code

1099226X

Code Ref.



TECHNICAL INFORMATION

Weight

0.13 lb