

TITO25 (Model)



TECHNICAL INFORMATION

[IES Files](#) 

Watt	2W
Luminaire	Up to 225lm
CCT	3000K – 4000K
CRI	>80
Wiring	700mA
LED life time	> 100000h - L80 - B20 (Ta 25°C)
Color	Stainless Steel - 30

DESCRIPTION

Construction

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- To be operated only with constant current 700mA Class 2 remote drivers (order separately).
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Clear PMMA screen.

Listings


- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP68 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Surface installation.
- AISI 316L stainless steel bracket.
- Supplied with power cord. 22AWG conductors.

IP68
40"


VERSIONS *(Click on below link to configure your product)*


[tito25](#)

Size:

Ø 0" 31/32

2" 1/4

3" 1/32

OPTICS




See accessories in the next page

AISI 316L STAINLESS STEEL PEG.

Arcluce Code **1099256X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 0.18 lb

PAINTED AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code **1099340X-12**

Code Ref.


**TECHNICAL INFORMATION****Color** Black - 12

Weight 0.11 lb

AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code **1099376X-30**

Code Ref.


**TECHNICAL INFORMATION****Color** Stainless Steel - 30

Weight 0.11 lb

THERMOPLASTIC MATERIAL PEG.

Arcluce Code **1099257X**

Code Ref.

**TECHNICAL INFORMATION****Weight** 0.11 lb
