

# TITO25 (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	2W	
Luminaire	Up to 225lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	700mA	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Stainless Steel - 30	

## **DESCRIPTION**

#### Construction

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

## **Electrical & Optics**

- To be operated only with constant current 700mA Class 2 remote drivers (order separately).
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Clear PMMA screen.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP68 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

## Installation

- Surface installation.
- AISI 316L stainless steel bracket.
- Supplied with power cord. 22AWG conductors.









# VERSIONS (Click on below link to configure your product)



# tito25

Size: Ø 0" 31/32 2" 1/4 3" 1/32

## **OPTICS**









See accessories in the next page




# AISI 316L STAINLESS STEEL PEG.

Arcluce Code

1099256X

Code Ref.



## **TECHNICAL INFORMATION**

Weight 0.18 lb

# PAINTED AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code Code Ref.

1099340X-12

Code Ref.



## **TECHNICAL INFORMATION**

Color	Black - 12
Weight	0.11 lb

# AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code

1099376X-30

Code Ref.



# **TECHNICAL INFORMATION**

Color	Stainless Steel - 30
Weight	0.11 lb

## THERMOPLASTIC MATERIAL PEG.

Arcluce Code Code Ref.

1099257X





# **TECHNICAL INFORMATION**

Weight 0.11 lb