

TITO55 (Model)



TECHNICAL INFORMATION		<u>IES Files</u> ↓
Watt	4W	
Luminaire	Up to 450lm	
ССТ	3000K – 4000K	
CRI	>80	
Wiring	350mA	
LED life time	> 60000h - L80 - B20 (Ta 25°C)	
Color	Stainless Steel - 30	

DESCRIPTION

Construction

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

Electrical & Optics

- To be operated only with constant current 350mA Class 2 remote drivers (order separately).
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 3/16" thermal-shock resistant tempered

Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP68 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

Installation

- Surface installation.
- AISI 316L stainless steel bracket.
- Supplied with power cord. 22AWG conductors.

IP68 40"







VERSIONS (Click on below link to configure your product)



tito55

Size: Ø 2" 5/32 3" 21/32 3" 3/16

OPTICS









See accessories in the next page



PAINTED AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code

1099019X-12

Code Ref.



TECHNICAL INFORMATION

Color	Black - 12
Weight	0.33 lb

AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code Code Ref.

1099319X-30



TECHNICAL INFORMATION

Color	Stainless Steel - 30
Weight	0.33 lb