

# TITO55 (Model)



## TECHNICAL INFORMATION

[IES Files](#) 

<b>Watt</b>	4W
<b>Luminaire</b>	Up to 450lm
<b>CCT</b>	3000K – 4000K
<b>CRI</b>	>80
<b>Wiring</b>	350mA
<b>LED life time</b>	> 100000h - L80 - B20 (Ta 25°C)
<b>Color</b>	Stainless Steel - 30

## DESCRIPTION

### Construction

- AISI 316L stainless steel body and trim.
- Silicone rubber gaskets.
- AISI 316 stainless steel external screws.

### Electrical & Optics

- To be operated only with constant current 350mA Class 2 remote drivers (order separately).
- High-efficacy LEDs with standard 3000K, 4000K (2700K or other CCTs available on request).
- PMMA lenses for LEDs.
- Screen made of 3/16" thermal-shock resistant tempered glass.

### Listings

- UL certified to U.S. and Canadian standards, suitable for wet locations (cULus mark).
- Rated IP68 per EN60598.
- Luminaire rated for -40°C minimum ambient temperature.
- High quality LED sources characterized according to IES TM-30, with high color consistency <3SDCM and long useful life >60000 hours at L80.

### Installation

- Surface installation.
- AISI 316L stainless steel bracket.
- Supplied with power cord. 22AWG conductors.

**IP68**  
40"


## VERSIONS *(Click on below link to configure your product)*


[tito55](#)

Size:

Ø 2" 5/32

3" 21/32

3" 3/16

## OPTICS



See accessories in the next page

## PAINTED AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code **1099019X-12**


Code Ref.

**TECHNICAL INFORMATION****Color** Black - 12**Weight** 0.33 lb

## AISI 316L STAINLESS-STEEL SLOPED VISOR.

Arcluce Code **1099319X-30**

Code Ref.

**TECHNICAL INFORMATION****Color** Stainless Steel - 30**Weight** 0.33 lb