

TULA Bollard (Model)



TECHNICAL INFORMATION

[IES Files](#) 

Watt	5W – 10W
Luminaire	Up to 525lm
CCT	3000K – 4000K
CRI	>80
Wiring	
LED life time	> 60000h - L80 - B20 (Ta 25°C)
Color	Grey - 16 / Aluminium - 21

DESCRIPTION



VERSIONS *(Click on below link to configure your product)*



[comfort](#)

Size:
5" 7/16
6" 13/32
23" 5/8 to 35" 7/16



[performance](#)

Size:
4" 19/32
6" 13/32
23" 5/8 to 35" 7/16




OPTICS



See accessories in the next page

ZINC-COATED AND PAINTED STEEL BASE PLATE WITH ZINC-COATED STEEL STUD BOLTS. 130 MM HIGH.

Arcluce Code **1099397X-16**
Code Ref.



TECHNICAL INFORMATION	
Color	Grey - 16
Weight	0.88 lb

IP68 LINEAR JOINT - 2 WAYS - 3 POLES.


Arcluce Code **1099409X**
Code Ref.



TECHNICAL INFORMATION	
Weight	0.07 lb

JUNCTION BOX IP68 - 4 WAYS - 2/3 POLES.


Arcluce Code **1099259X**
Code Ref. **O7932**



TECHNICAL INFORMATION	
Weight	0.11 lb

GALVANIZED AND PAINTED STEEL BASE PLATE WITH GALVANIZED STEEL STUD BOLTS. 130 MM HIGH.

Arcluce Code **1099397X-21**
Code Ref.



TECHNICAL INFORMATION	
Color	Aluminium - 21
Weight	0.88 lb